



(19)

(11) Publication number:

08094452 A

Generated Document.

PATENT ABSTRACTS OF JAPAN

(21) Application number: **06226138**

(51) Intl. Cl.: **G01K 7/22 H01C 1/028 H01C 7/04**

(22) Application date: **21.09.94**

(30) Priority:

(43) Date of application
publication: **12.04.96**

(84) Designated contracting
states:

(71) Applicant: **MITSUBISHI MATERIALS CORP**

(72) Inventor: **ITO HIDEO**
SUGIYAMA OSAMU
NAKAGAWA TERUO

(74) Representative:

(54) RESIN MOLDED THERMISTOR SENSOR

(57) Abstract:

PURPOSE: To obtain a resin molded thermistor sensor excellent in moisture resistance and heat shock resistance by injecting a specified urethane resin, as a mold resin, into the protective case for thermistor element.

CONSTITUTION: A thermistor element 1 connected with an insulated wire 4 is inserted into a protective case 5 injected with a liquid resin (mold resin) 6 or the liquid resin is injected after the thermistor element 1 is inserted into the protective case 5. Subsequently, the liquid resin 6 is cured to produce a resin molded thermistor. A two-liquid curing polybutadiene based urethane resin is employed as the mold resin. Cross-linked polyethylene or polyvinyl chloride is employed as the insulation coating 3 for the wire 4 and an epoxy resin or a moisture curing urethane resin is applied, as a plier, onto the surface of the insulation coating 3. This structure prevents interfacial delamination due to stress caused by differential thermal expansion thus ensuring high reliability for a long term.

